



SEMI SYNTHETIC SAE 10W-40 API SP MV19

ENGINE LUBRICANT USING MOLYBDENUM DITHIOCARBAMATE AS AN ANTIOXIDANT TOP TREATMENT IN HIGH SULFUR BASE STORES

Product Description:

MOMO RACING Semi Synthetic 10W-40 is an environmentally responsible, part-synthetic automotive engine oil designed to provide excellent engine protection for both turbocharged gasoline direct injection, conventional gasoline-fueled and flex-fueled passenger cars, vans, CUVs, SUVs and light trucks under all operating conditions. It is formulated with a blend of synthetic and highly refined virgin base stocks. Semi Synthetic engine oil is formulated to provide excellent wear protection, to minimize sludge and varnish formation, and to resist viscosity and thermal breakdown, outstanding low temperature fluidity. It also protects against rust and bearing corrosion, and is resistant to foaming. The part-synthetic formulation provides enhanced performance benefits at extreme temperatures compared with conventional engine oils, for extra protection under all driving conditions. MOMO RACING Semi Synthetic 10W-40 engine oils are formulated to exceed the latest API Service Classification for gasoline engines, as well the latest API SP standard. It is uniquely formulated to help combat low speed pre-ignition (LSPI) in turbocharged gasoline direct injection engines. They also provide enhanced protection for the latest emission control systems and long engine life by lubricating critical parts effectively.

- Flow better at low temperatures than conventional engine oils for extra protection during cold starts.
- Reduces formation of varnish, sludge and carbon deposits on engine to keep your car running cleaner longer.

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		10W40
Colour		ASTM1500	L2.5
Density @ 15 °C	kg/m3		0.85
Kinematic Viscosity @ 40°C	cSt	ASTM D445	92.95
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.20
Viscosity Index		ASTM D2270	158

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.



**THE FUTURE OF RACING MOBILITY
MAXIMIZE YOUR PERFORMANCE**