



MULTIGRADE ENGINE OIL

SAE 15W-40

API SM/CF MX40

ENGINE LUBRICANT USING MOLYBDENUM DITHIOCARBAMATE AS AN ANTIOXIDANT TOP TREATMENT IN HIGH SULFUR BASE STORES

Product Description:

MOMO RACING Premium Mineral 15W-40 Engine Oil is formulated with virgin mineral base oils and high-performance additives which provide optimum performance and protection to most late model engines. MOMO RACING Premium Mineral 15W-40 Engine Oil promotes easier cold starting, reduces wear and keeps the engine clean between the recommended oil drain intervals. High-temperature stability provides increased oxidation control in both turbocharged and non-turbocharged engines.

- Maintains viscosity at high temperature
- Anti-wear protection to extend the life of the engine
- Enhanced detergency to clean and prevent sludge formation
- Contains anti-oxidants to prolong the life of the oil between drain intervals
- Faster oil flow improves cold starting
- Safe for catalytic converters

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		15W40
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.85
Kinematic Viscosity @ 40°C	cSt	ASTM D445	108.20
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.30
Viscosity Index		ASTM D2270	135

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.



THE FUTURE OF RACING MOBILITY
MAXIMIZE YOUR PERFORMANCE