



MULTIGRADE ENGINE OIL

SAE 20W-50

API SL/CF MX50

ENGINE LUBRICANT USING MOLYBDENUM DITHIOCARBAMATE AS AN ANTIOXIDANT TOP TREATMENT IN HIGH SULFUR BASE STORES

Product Description:

MOMO RACING Premium Mineral 20W-50 Engine Oil is formulated with virgin mineral base oils and high-performance additives which provides ultimate protection for older or worn engines. This premium engine oil is formulated for use all petrol and diesel engines requiring a SAE 20W-50 multigrade engine oil. Premium Mineral 20W-50 Engine Oil helps to reduce oil consumption, reduces further wear and protects the engine between recommended oil drain intervals.

- Designed to protect higher kilometre engines from wear
- Increased viscosity slows oil loss or burning
- Extra oil film strength quietens worn engines
- Prevents sludge build-up from possible fuel contaminants
- Maintains viscosity at high temperatures
- Safe for catalytic converters

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		20W50
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.87
Kinematic Viscosity @ 40°C	cSt	ASTM D445	181.25
Kinematic Viscosity @ 100°C	cSt	ASTM D445	19.40
Viscosity Index		ASTM D2270	123

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.



THE FUTURE OF RACING MOBILITY
MAXIMIZE YOUR PERFORMANCE