



AUTOMATIC TRANSMISSIONS FLUID GM DEXRON III

DEXRON III / IIE
FORD MERCON

ALLISON C4
CATERPILLAR TO-2

Product Description:

MOMO RACING ATF DEXRON III is an advanced technology premium mineral, multi vehicle, red coloured. It is manufactured from the latest additive technology and advanced hydrocracked base oils along with a viscosity modifier to minimize shear loss and provide outstanding performance through the life of the fluid. ATF DEXRON III is designed for use in passenger cars, light and heavy duty truck automatic transmissions, power steering units, rotary vane and screw type compressors, hydraulic systems and manual transmissions where this type of fluid is specified.

ATF DEXRON III is suitable for use where GM Dexron® III & IIIE are recommended and can also be used wherever GM Dexron® II type fluids were recommended.

Note:

Not for use in 6 and 8 speed ZF transmissions or 7 speed Mercedes Benz transmissions.

Not for use in Direct-Shift or Dual Clutch Gearboxes(DSG/ DCT) or Continuously Variable Transmissions(CVT)
Please refer to service manual of Recommendation Guide for the correct applications.

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade			Dexron III
Colour		ASTM1500	Red L5.0
Density @ 15 °C	kg/m3		0.85
Kinematic Viscosity @ 40°C	cSt	ASTM D445	39.38
Kinematic Viscosity @ 100°C	cSt	ASTM D445	7.13
Viscosity Index		ASTM D2270	146

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves.

If skin contact occurs, wash immediately with soap and water.

Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil.

Dispose of container as per EPA guidelines.

Do not use this container for fuel or solvents.



**THE FUTURE OF RACING MOBILITY
MAXIMIZE YOUR PERFORMANCE**