



SEMI SYNTHETIC SAE 10W40 DIESEL TURBO MD10 API CK-4/SN

ACEA E9-2012 /E7-08 . Daimler MB 228.31 . MTU Category 2.1
MAN M3575 . FORD WSS M2C171-F1 . Renault RLD-4/RLD-3
DFS 93K218/DFS 93K215 . Caterpillar ECF-3/ECF-2
Detroit DIESEL DFS 93K222 . Mack EO-O Premium Plus/EO-N
Volvo VDS-4.5/VDS-4/VDS-3 . Cummins CES20086/CES 20081

ENGINE LUBRICANT USING MOLYBDENUM DITHIOCARBAMATE AS AN ANTIOXIDANT TOP TREATMENT IN HIGH SULFUR BASE STORES

Product Description:

MOMO RACING Diesel Turbo10W40 is formulated with Synthetic and hydro-cracked base stocks and a tailored additive package that helps extend engine life. Proprietary formulation delivers excellent wear protection, outstanding oxidation stability, and outstanding TBN retention with long oil drain interval. Diesel Turbo 10W40 is an advanced semi synthetic heavy-duty diesel engine oil which ensures maximum soot handling performance and excellent wear protection on on-road and off-road vehicles or equipment requiring a 10W40 API CK-4 engine oil. Designed to meet the demanding requirements of most OEMs in new and older engines of trucks, buses, construction machineries, farming equipment, mining, generators, fishing vessels, and other applications fitted with Exhaust Gas Recirculation (EGR) and driven by EPA / NHTSA requirement. Perfect for use in engines with or without Diesel Particulate Filters (DPF). Promotes longer component and engine life. Used for diesel fuels with sulfur content of up to 0.05% by weight.

Recommended for mixed fleets applications – diesel and gasoline engines. For new & old generation engines. Suitable for classic cars, trucks, light commercial vehicles, agricultural machineries and other on-road & off-road systems requiring a 10W40 API CK-4 or API SN or ACEA E9 engine oils. For diesel engines meeting Euro 1, Euro 2, Euro-3, Euro-4, Euro-5 and Euro 6 emission requirements.

Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		10W40
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.85
Kinematic Viscosity @ 40°C	cSt	ASTM D445	101.92
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.99
Viscosity Index		ASTM D2270	154

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.



**THE FUTURE OF RACING MOBILITY
MAXIMIZE YOUR PERFORMANCE**