



# MULTIGRADE ENGINE OIL

## SAE 15W-40 DIESEL TURBO MD15

API CI-4/SL . ACEA E7-16 . Cummins CES20076 / CES20077  
 Caterpillar ECF-2/1A . MB 228.3 (ver.2017.1) . MAN M3275  
 Deutz DQC III-18 . Detroit DFS 93K215 . Mack EO-M, EO-M PLUS  
 MTU Category 2 . Mack EO-N . Renault RLD-2 . Volvo VDS-3

### ENGINE LUBRICANT USING MOLYBDENUM DITHIOCARBAMATE AS AN ANTIOXIDANT TOP TREATMENT IN HIGH SULFUR BASE STORES

#### Product Description:

MOMO RACING DIESEL TURBO 15W-40 is an extra high performance universal engine oil designed for high loaded diesel engines in light and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and this product is suitable for vehicles equipped with DPF filters. Premium base oils combined with detergents prevent oil thickening and soot build-up which keeps the engine cleaner and cooler for longer. Diesel Turbo Engine Oil also protects critical engine components from other harmful substances created during combustion. Formulated to provide the highest level of protection for diesel engines, large or small, non-turbocharged and turbocharged. MOMO RACING DIESEL TURBO 15W-40 is formulated with premium quality hydrotreated base stock in combination with a special additive package to meet API CI-4/SL specifications.

- Keep internals cool while reducing soot and deposits during continuous heavy torque loads
- For light diesel and heavy-duty diesel vehicles, both direct and indirect injection engines
- Suits both turbocharged and non-turbocharged diesel engines
- Excellent low-temperature, cold-start performance
- Superior deposit control and valve train protection in modern high-performance and high-speed diesel engines

#### Typical Physical Characteristics

PROPERTY TEST	UNITS	METHODS	RESULT
Viscosity Grade	SAE J300		15W40
Colour		ASTM1500	L2.0
Density @ 15 °C	kg/m3		0.86
Kinematic Viscosity @ 40°C	cSt	ASTM D445	109.75
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.80
Viscosity Index		ASTM D2270	140

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

**CAUTION:** Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.



**THE FUTURE OF RACING MOBILITY  
 MAXIMIZE YOUR PERFORMANCE**